

TECHNICAL DATA SHEET

DESCRIPTION AND AREAS OF USE

Waterproofing membrane consisting of non-woven polyester coated with plastomer bitumen. With slate layer in either Charcoal, Slate, White, Red, or Green.

FINISHING

- Top surface finished with a mechanically rolled slate layer offering excellent bonding with PP film on the 8cm selvedge edge.
- Underside finished with a thermofusible film.

APPLICATION

- Cap sheet in multi-layer waterproofing system.

COMPOSITION

- Reinforcement: non-woven polyester
- Coating mass: Plastomeric Bitumen

TECHNICAL SPECIFICATIONS (AVERAGE VALUES)

- Tensile strength (EN 12311-1)
 - longitudinal: 650 N
 - transversal: 500 N
- Elongation at break (EN 12311-1)
 - longitudinal: 40 %
 - transversal: 40 %
- Resistance to heat (EN 1110): > 140°C
- Low temperature flexibility (EN 1109): -8°C
- Dimensional stability (EN 1107-1): ≤ 0,5 %

DIMENSIONS

- Thickness : 4 mm
- Length : 7.5 m
- Width : 1 m
- Surface : 7.5 m²
- Average weight : 43 kg
- Colour : Charcoal, Slate, White, Red, or Green

FIXING

Torching method with asphalt burner.

SAFETY, STORAGE & HANDLING INFORMATION

- Do not pile pallets.
- Store indoors.

TECHNICAL DATA SHEET

TRANSPORT CLASSIFICATION

N/A

The information in this product data sheet is based on our experience and testing. It represents the latest information available at the time of printing, but no guarantee of its accuracy is made or implied, nor responsibility taken for use to which this information may be put. We reserve the right to alter or up-date information parameters and formulations at any time without notice.

Nuraply 3PM