



## PRODUCT DETAILS

- Use:** Nuraply All Season Sprayable Bonding Adhesive is an aerosol bonding adhesive that can be used for Nuraply TPO adhered roofing systems and wall flashings. The Nuraply All Season adhesive complies to Low VOC requirements and is a contact adhesive requiring two-sided application.
- Type:** Two-sided sprayable aerosol adhesive for hot or cold applications with fast drying properties in a pressurized canister.
- Substrates:** Compatible with the following field and wall applications/boards/substrates: Polyisocyanurate; gypsum; concrete; treated plywood, cement board.
- Colour:** Light green

## INSTALLATION/APPLICATION

- Install when ambient temperature is  $-39^{\circ}\text{C}$  and rising and with the adhesive canister temperature at a minimum  $21^{\circ}\text{C}$ .
- Ensure all surfaces are dry, clean and free of debris prior to application.
- Do not install with direct contact to asphalt.
- Refer to the detailed application instructions and guidelines for proper installation and coverage rates.
- Coverage rates are dependent on the membrane type and substrate surfaces. Installation instructions are available in the Nuraply TPO Application Guide.

## ENERGY AND THE ENVIRONMENT

|  |          |
|--|----------|
| Maximum VOC  | <250 g/l |
| This product may be used in jurisdictions limiting VOC (volatile organic compounds) content of single ply roofing adhesive to no greater than 250 g/l. |          |

## PACKAGING AND COVERAGE

|                          |                            |
|--------------------------|----------------------------|
| Container Weight         | 20.41kg canister           |
| Vertical Coverage Rate   | 70m <sup>2</sup> /cylinder |
| Horizontal Coverage Rate | 93m <sup>2</sup> /cylinder |

\* Coverage, open and dry time rates can vary dramatically depending on the particular substrate and environmental conditions. Coverage rates stated herein are approximate only.

## STORAGE

|                           |   |
|---------------------------|---|
| Shelf Life                | 12 months from manufacture date   |
| Storage Conditions        | Clean, dry, indoor environment, in a well-ventilated area, and in an unopened container, tightly sealed.      |
| Temperature Range         | $-3.9^{\circ}\text{C}$ - $37.8^{\circ}\text{C}$ . Do not let freeze. Do not let exceed $43^{\circ}\text{C}$ . |
| Installation Conditioning | Bring the adhesive to a minimum of $21^{\circ}\text{C}$ and maintain for installation and use.                |

## PRECAUTIONS

This product is flammable. Adhesive contains ingredients which could be harmful if mishandled. Contact with skin and eyes should be avoided, and the recommended personal protective equipment should be worn. This adhesive is in a pressurized container and should be used with caution.

## TRANSPORT CLASSIFICATION

3

*The information in this product data sheet is based on our experience and testing. It represents the latest information available at the time of printing, but no guarantee of its accuracy is made or implied, nor responsibility taken for use to which this information may be put. We reserve the right to alter or up-date information parameters and formulations at any time without notice.*

