

CERTIFICATE NO: CM70032 Rev1

Date of issue: 17 June 2022

1 CERTIFICATE HOLDER DETAILS

Nuralite Waterproofing Ltd

60D Leon Leicester Avenue, Mt Wellington, Auckland 1060 New Zealand

Email: info@nuralite.co.nz Ph: 09 579 2046 www.nuralite.co.nz



PRODUCT CERTIFICATION BODY

Bureau Veritas Australia Pty Ltd

3/435 Williamstown Road Port Melbourne VIC 3207 Australia

Ph: 1800 855 190 www.bureauveritas.com.au

Bureau Veritas Australia Pty Ltd

The complaints process for this certificate can be found here:

www.bureauveritas.com.au/your-feedback

PRODUCT CERTIFICATE



Nuraply 3PM Torch-on Membrane for Roofs and Decks

KEY INFORMATION

SUMMARY OF DESCRIPTION OF BUILDING METHOD OR PRODUCT

Nuraply 3PM system is a tough, reinforced, double-layer torch-on bituminous waterproofing membrane system for new and existing roofs and decks. Nuraply 3PM capsheet is used with one of the Basesheet options:

- Nuraply 3PB
- Nuraply 3PB-SA
- Nuraply 3PV
- Nuraply 3PV-SA

The Nuraply 3PM torch-on membrane system may also incorporate Enertherm PIR insulation board.

Continuation of description can be found in item 9. Supporting Information about Description of Building Product or Method.

Matters that should be taken into account in the use or application of the building method or product can be found in item 6. Conditions and Limitations of Use

4 SUMMARY OF INTENDED USE OF BUILDING METHOD OR PRODUCT

The Nuraply 3PM double layer torch on membrane system provides a durable waterproofing system for installation by approved installers, on new and existing roofs and decks of any size.

Continuation of intended use can be found in item 8. Supporting Information about Intended use of Building Product or Method.

BUILDING CODE PROVISIONS

The performance clauses of the New Zealand Building Code that are relevant to the intended use and with which the building method or product complies or contributes to (where used as part of a system).

B2 Durability: B2.3.1(b)

E2 External Moisture: E2.3.1 (contributes to), E2.3.2, E2.3.7

F2 Hazardous Building Materials: F2.3.1

How the building method or product complies or contributes can be found in item 12. Basis for Certification. Any qualifications on the extent of that compliance can be found in item 6. Conditions and limitations of use.



This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification accreditation body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004.

The Ministry does not in any way warrant, guarantee, or represent that the building method or product that is the subject of this certificate conforms with the New Zealand Building Code, nor accept any liability arising out of the use of the building method or product. The Ministry disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages, and costs arising as a result of the use of the building method(s) or product(s) referred to in this certificate.



PRODUCT CERTIFICATE



Nuraply 3PM Torch-on Membrane for Roofs and Decks

6 CONDITIONS AND LIMITATIONS OF USE

- 1. Nuraply 3PM torch-on membrane shall be installed in accordance with the Nuraply 3PM Roofing Membrane Installation Manual Edition 1 March 2019, by a Nuralite Waterproofing Ltd approved installer (see www.nuralite.co.nz/applicator to find an approved installer).
- 2. Where a Nuraply membrane is applied to a timber substrate the timber shall be preservative treated. Such preservative treatments shall not be LOSP (light organic solvent preservative) or CuN (copper nitrate).
- 3. Nuraply 3PM torch-on membrane is suitable only for light maintenance foot traffic.
- 4. Nuraply 3PM torch-on membrane shall have a minimum finished fall (excluding gutters) of 1:80.
- 5. It may be installed on a cold roof with insulation installed below the substrate or as a warm roof (known as Nuratherm) with Enertherm insulation installed above the substrate.
- 6. The system shall only be used with the following substrates:
 - H3.2 treated Timber, including plywood sheets and reconstituted wood panels (Strandboard), timber substrates complying with AS/NZ 2269:2012 (directly or with Enertherm PIR Boards between) with treated timber trim, battens and framing where timber is detailed and Nuralite product is directly applied
 - Concrete substrates complying with NZS 3101:2006 or NZS 3114:1987 (directly or with Enertherm PIR Boards between)
 - NPM 900 metal tray decks with Enertherm PIR boards between.
- 7. The system may be installed in NZS 3604:2011 Wind Zones, up to and including Extra High.
- 8. Ventilation of timber roof spaces must be specifically designed.

NOTE: Together, items 3, 4, 5 and 6 define scope of use.

HEALTH AND SAFETY INFORMATION

The compliance with any manufacturer's installation instructions, maintenance, OH & S statements, MSDS's and other Health and Safety declarations will provide the necessary Health and Safety Information pertaining to the product.

3 SIGNATURES

Sam Guindi

Product Certification Manager

For and on behalf of

Bureau Veritas Australia Pty Ltd

Jono Burton Technical Manager For and on behalf of Nuralite Waterproofing Ltd

