

Date of issue: 4.02.22 NZ Safety Data Sheet

1. Identification of the Substance/Mixture and Supplier.

Product Name: NURAFLUX PRIMER QD

Uses: Bitumen primer

Supplier: Nuralite Waterproofing Ltd

60D Leon Leicester Avenue

Mt Wellington Auckland 1060 New Zealand. +64 9 579 2046

Telephone: +64 9 579 2046 Web: www.nuralite.co.nz

Emergency Telephone: 027 5350899 (General Manager) – 24 hrs National Poisons Centre Tel: 0800 POISON (0800 764766) – 24 hrs

2. Hazards Identification.

Hazardous Status: Classified as hazardous according to the criteria of HSNO.

DG Status: Classified as Dangerous Goods according to NZS5433

НА	ZARD CLASSIFICATIONS	HAZARD STATEMENTS	GHS Pictogram
Flammable liqu	uids, Cat 3	H226 Flammable liquid and vapour.	(3)
		H304 May be fatal if swallowed and enters airways.	&
STOT-SE, Cat	3	H336 May cause drowsiness or dizziness.	
Aquatic toxicity	(Chronic), Cat 3	H412 Harmful to aquatic life with long lasting effects.	
Signal Word:		DANGER	
PREVENTION	STATEMENTS		
P102	Keep out of reach of children.		
P103	Read label before use.		
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.		
P233	Keep container tightly closed.		
P240	Ground/bond container and receiving equipment.		
P241	Use explosion-proof electrical/ventilating/lighting equipment.		
P242	Use only non-sparking tools.		
P243	Take precautionary measures against static discharge.		
P261	Avoid breathing mist/vapours/spray.		
P271	Use only outdoors or in a well ventilated area.		
P273	Avoid release to the environment.		
P280 Wear protective gloves/protective clothing/eye protection/face protection.			
RESPONSE STATEMENTS			
P370 + P378		n dioxide or dry chemical powder for extinction.	
P101		e product container or label at hand.	
P301 + P310		call a POISON CENTER or doctor/physician.	
P331	Do NOT induce vomiting.		
P304 + P340	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.		

fighters

fire-fighters

Special precautions for

Special protective

equipment for fire



Date of issue: 4.02.22 NZ Safety Data Sheet

Date of issue:	4.02.22	NZ Safety Data Sheet		
P312	Call a POISON CENTER or doctor/physician if you feel unwell.			
P303 + P361	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin			
+ P353	with water/shower.			
STORAGE STA	ATEMENTS			
P403 + P235	Store in a well-ventilated place. Keep cool.			
P233	Keep container tightly closed.			
P405	Store locked up.			
DISPOSAL STATEMENTS				
P501		uct enter the environment.	Do not dispose of in waterways or sewers.	
			azardous waste, via a licensed facility. See	
		posal/recycling information		
		, , , ,		
3. Compo	sition/Information	on Ingredients.		
		3		
Chemical Entit	:V	CAS Number	Proportion %w/w	
	C9-C10, n-alkanes,	1174921-73-3	50-75	
iso-alkanes, cyc				
aromatics				
	edients: Non-hazardo	ous, or below the hazardou	s threshold.	
		,		
4. First Aid Measures.				
Swallowed	Swallowed If swallowed do NOT induce vomiting. Give water to drink. Get medical attention if symptoms occur.			
Inhaled	If inhaled, move the victim to fresh air immediately. Begin artificial respiration if breathing has stopped. Obtain medical attention if symptoms occur.			
Eye Contact				
Lyc Comact	attention if irritation occurs.			
Skin Contact			ve contaminated clothing and flush skin and	
hair with running water. Get medical attention if symptoms occur.				
Further Information For advice		dvice contact the National Poisons Centre – 0800 POISON (0800 764 766)		
– or a doctor, immediately.				
5. Fire-Fighting Measures.				
Suitable exting media	guishing In case	of fire, use water spray (fog	g), foam, dry chemical or CO2.	
Unsuitable extinguishing				
Hazards from t				
Hazardous cor	nbustion Decomp	position products may inclu	de:	
products				
		, , , , , , , , , , , , , , , , , , , ,		

without suitable training.

mode.

Promptly isolate the scene by removing all persons from the vicinity of the

incident if there is a fire. No action shall be taken involving any personal risk or

Fire-fighters should wear appropriate protective equipment and self-contained

breathing apparatus (SCBA) with a full face-piece operated in positive pressure



Date of issue: 4.02.22 NZ Safety Data Sheet

Date of issue: 4.02.22		
6. Accidental Release Measures.		
Personal precautions	Wear appropriate Personal Protective Equipment (see section 8). Provide adequate ventilation.	
Environmental	Avoid dispersal of spilt material and runoff and contact with soil, waterways,	
precautions	drains and sewers. Inform the relevant authorities if the product has caused	
precautions	environmental pollution (sewers, waterways, soil or air).	
Small spill	Stop leak if without risk. Move containers from spill area. Dilute with water and	
oman opin	mop up if water-soluble or absorb with an inert dry material and place in an	
	appropriate waste disposal container. Use spark-proof tools and explosion-proof	
	equipment. Dispose of via a licensed waste disposal contractor.	
Large spill	Stop leak if without risk. Move containers from spill area. Prevent entry into	
3 - 1	sewers, water courses, basements or confined areas. Contain and collect spills	
	with non-combustible, absorbent material e.g. sand, earth, vermiculite or	
	diatomaceous earth and place in container for disposal according to local	
	regulations (see section 13). Use spark-proof tools and explosion-proof	
	equipment. Dispose of via a licensed waste disposal contractor. Contaminated	
	absorbent material may pose the same hazard as the spilt product.	
7. Handling and St	torage.	
11 11'	TW	
Handling	Wear appropriate PPE, and ensure there is adequate ventilation and extraction in	
	the work area. Avoid skin or eye contact, or breathing in the product. Follow	
	precautions listed in section 2 for handling flammable/combustible liquids.	
Ctanana		
Storage	Keep container dry and tightly closed, in a cool, well-ventilated area, away from	
-	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight.	
8. Exposure Contr	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. ol/Personal Protection	
-	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. ol/Personal Protection	
8. Exposure Contr	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. ol/Personal Protection	
8. Exposure Contr	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. ol/Personal Protection not available	
8. Exposure Contr Exposure Standards – r Engineering Controls	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. ol/Personal Protection not available General ventilation and local exhaust should be suitable to keep vapour	
8. Exposure Contr	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. ol/Personal Protection not available General ventilation and local exhaust should be suitable to keep vapour concentrations minimised. Ventilation equipment should be explosion-proof when	
8. Exposure Contr Exposure Standards – r Engineering Controls	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. ol/Personal Protection not available General ventilation and local exhaust should be suitable to keep vapour concentrations minimised. Ventilation equipment should be explosion-proof when	
8. Exposure Contr Exposure Standards – r Engineering Controls	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. ol/Personal Protection not available General ventilation and local exhaust should be suitable to keep vapour concentrations minimised. Ventilation equipment should be explosion-proof when	
8. Exposure Contr Exposure Standards – r Engineering Controls	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. ol/Personal Protection not available General ventilation and local exhaust should be suitable to keep vapour concentrations minimised. Ventilation equipment should be explosion-proof when	
8. Exposure Contr Exposure Standards – r Engineering Controls	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. ol/Personal Protection ot available General ventilation and local exhaust should be suitable to keep vapour concentrations minimised. Ventilation equipment should be explosion-proof when operating in flammable zones.	
8. Exposure Contr Exposure Standards – r Engineering Controls	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. ol/Personal Protection ot available General ventilation and local exhaust should be suitable to keep vapour concentrations minimised. Ventilation equipment should be explosion-proof when operating in flammable zones. Wear a vapour respirator.	
8. Exposure Controls Exposure Standards – r Engineering Controls Personal Protection Respiratory Eyes	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. ol/Personal Protection General ventilation and local exhaust should be suitable to keep vapour concentrations minimised. Ventilation equipment should be explosion-proof when operating in flammable zones. Wear a vapour respirator. Wear chemical goggles/face protection.	
8. Exposure Controls Exposure Standards – r Engineering Controls Personal Protection Respiratory Eyes Hands	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. ol/Personal Protection General ventilation and local exhaust should be suitable to keep vapour concentrations minimised. Ventilation equipment should be explosion-proof when operating in flammable zones. Wear a vapour respirator. Wear chemical goggles/face protection. Wear chemical gloves – PVC, Polychlorpropene or Nitrile.	
8. Exposure Controls Exposure Standards – r Engineering Controls Personal Protection Respiratory Eyes	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. ol/Personal Protection General ventilation and local exhaust should be suitable to keep vapour concentrations minimised. Ventilation equipment should be explosion-proof when operating in flammable zones. Wear a vapour respirator. Wear chemical goggles/face protection.	
8. Exposure Contr Exposure Standards – r Engineering Controls Personal Protection Respiratory Eyes Hands Other	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. ol/Personal Protection The direct sunlight available General ventilation and local exhaust should be suitable to keep vapour concentrations minimised. Ventilation equipment should be explosion-proof when operating in flammable zones. Wear a vapour respirator. Wear chemical goggles/face protection. Wear chemical gloves – PVC, Polychlorpropene or Nitrile. Wear overalls or dust coat. Use PVC apron when handling large quantities.	
8. Exposure Controls Exposure Standards – r Engineering Controls Personal Protection Respiratory Eyes Hands	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. ol/Personal Protection The direct sunlight available General ventilation and local exhaust should be suitable to keep vapour concentrations minimised. Ventilation equipment should be explosion-proof when operating in flammable zones. Wear a vapour respirator. Wear chemical goggles/face protection. Wear chemical gloves – PVC, Polychlorpropene or Nitrile. Wear overalls or dust coat. Use PVC apron when handling large quantities.	
8. Exposure Controls Engineering Controls Personal Protection Respiratory Eyes Hands Other 9. Physical and Ch	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. ol/Personal Protection ot available General ventilation and local exhaust should be suitable to keep vapour concentrations minimised. Ventilation equipment should be explosion-proof when operating in flammable zones. Wear a vapour respirator. Wear chemical goggles/face protection. Wear chemical gloves – PVC, Polychlorpropene or Nitrile. Wear overalls or dust coat. Use PVC apron when handling large quantities.	
8. Exposure Controls Exposure Standards – r Engineering Controls Personal Protection Respiratory Eyes Hands Other 9. Physical and Cheres PROPERTY	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. ol/Personal Protection ot available General ventilation and local exhaust should be suitable to keep vapour concentrations minimised. Ventilation equipment should be explosion-proof when operating in flammable zones. Wear a vapour respirator. Wear chemical goggles/face protection. Wear chemical gloves — PVC, Polychlorpropene or Nitrile. Wear overalls or dust coat. Use PVC apron when handling large quantities. SPECIFICATION	
8. Exposure Controls Exposure Standards – r Engineering Controls Personal Protection Respiratory Eyes Hands Other 9. Physical and Cheres PROPERTY Physical state	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. ol/Personal Protection General ventilation and local exhaust should be suitable to keep vapour concentrations minimised. Ventilation equipment should be explosion-proof when operating in flammable zones. Wear a vapour respirator. Wear chemical goggles/face protection. Wear chemical gloves – PVC, Polychlorpropene or Nitrile. Wear overalls or dust coat. Use PVC apron when handling large quantities. SPECIFICATION Liquid	
8. Exposure Controls Exposure Standards – r Engineering Controls Personal Protection Respiratory Eyes Hands Other 9. Physical and Cr PROPERTY Physical state Colour	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. Ol/Personal Protection The available General ventilation and local exhaust should be suitable to keep vapour concentrations minimised. Ventilation equipment should be explosion-proof when operating in flammable zones. Wear a vapour respirator. Wear chemical goggles/face protection. Wear chemical gloves – PVC, Polychlorpropene or Nitrile. Wear overalls or dust coat. Use PVC apron when handling large quantities. The available SPECIFICATION Liquid Black	
8. Exposure Controls Exposure Standards – r Engineering Controls Personal Protection Respiratory Eyes Hands Other 9. Physical and Cher PROPERTY Physical state Colour Odour	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. Ol/Personal Protection The available General ventilation and local exhaust should be suitable to keep vapour concentrations minimised. Ventilation equipment should be explosion-proof when operating in flammable zones. Wear a vapour respirator. Wear chemical goggles/face protection. Wear chemical gloves – PVC, Polychlorpropene or Nitrile. Wear overalls or dust coat. Use PVC apron when handling large quantities. Perior like SPECIFICATION Liquid Black Petrol-like	
8. Exposure Controls Engineering Controls Personal Protection Respiratory Eyes Hands Other 9. Physical and Cheres PROPERTY Physical state Colour Odour pH	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. Ol/Personal Protection The available General ventilation and local exhaust should be suitable to keep vapour concentrations minimised. Ventilation equipment should be explosion-proof when operating in flammable zones. Wear a vapour respirator. Wear chemical goggles/face protection. Wear chemical gloves – PVC, Polychlorpropene or Nitrile. Wear overalls or dust coat. Use PVC apron when handling large quantities. The mical Properties SPECIFICATION Liquid Black Petrol-like Not determined	
8. Exposure Controls Engineering Controls Personal Protection Respiratory Eyes Hands Other 9. Physical and Cheres PROPERTY Physical state Colour Odour pH Boiling Pt	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. Ol/Personal Protection The available General ventilation and local exhaust should be suitable to keep vapour concentrations minimised. Ventilation equipment should be explosion-proof when operating in flammable zones. Wear a vapour respirator. Wear chemical goggles/face protection. Wear chemical gloves – PVC, Polychlorpropene or Nitrile. Wear overalls or dust coat. Use PVC apron when handling large quantities. The available SPECIFICATION Liquid Black Petrol-like Not determined 145°C	
8. Exposure Controls Engineering Controls Personal Protection Respiratory Eyes Hands Other 9. Physical and Cr PROPERTY Physical state Colour Odour pH Boiling Pt Solids content	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. ol/Personal Protection not available General ventilation and local exhaust should be suitable to keep vapour concentrations minimised. Ventilation equipment should be explosion-proof when operating in flammable zones. Wear a vapour respirator. Wear chemical goggles/face protection. Wear chemical gloves – PVC, Polychlorpropene or Nitrile. Wear overalls or dust coat. Use PVC apron when handling large quantities. specification Liquid Black Petrol-like Not determined 145°C 46%	
8. Exposure Controls Engineering Controls Personal Protection Respiratory Eyes Hands Other 9. Physical and Cheres PROPERTY Physical state Colour Odour pH Boiling Pt	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. Ol/Personal Protection The available General ventilation and local exhaust should be suitable to keep vapour concentrations minimised. Ventilation equipment should be explosion-proof when operating in flammable zones. Wear a vapour respirator. Wear chemical goggles/face protection. Wear chemical gloves – PVC, Polychlorpropene or Nitrile. Wear overalls or dust coat. Use PVC apron when handling large quantities. The available SPECIFICATION Liquid Black Petrol-like Not determined 145°C	

NURAFLUX PRIMER QD



Date of issue: 4.02.22 NZ Safety Data Sheet

	UEL: 7% (vol)
Vapour pressure	5 hPa
Density	0.86 kg/L @ 20°C
Solubility	Insoluble in water
Viscosity, kinematic	9-14 mm ² /s @ 40°C
Ignition temperature	240°C
VOC	430 g/L

10. Stability and Reactivity

Stability	The product is stable
Possibility of	Under normal conditions of storage and use, hazardous reactions will not occur.
hazardous reactions	
Conditions to avoid	No data
Incompatible materials	No data
Hazardous	Under normal conditions of storage and use, hazardous decomposition products
decomposition	should not be produced.
products	

11. Toxicological Information

Data sourced from supplier (IKO)

Acute Oral Toxicity	Not Classified
Acute Dermal Toxicity	Not Classified
Acute Inhalation Toxicity	Not Classified
Aspiration Hazard	May be fatal if swallowed and enters airways.
Skin Irritancy/Corrosion	Not Classified
Eye Irritancy/Corrosion	Not Classified
Respiratory Sensitisation	Not Classified
Skin Sensitisation	Not Classified
Mutagenic	Not Classified
Carcinogenic	Not Classified
Reproductive/Development	Not Classified
Toxicity	
STOT-SE	May cause drowsiness or dizziness.
STOT-RE	Not Classified
Toxicity STOT-SE	May cause drowsiness or dizziness.

Toxicity Data

Product Acute Toxicity Estimate

ORAL LD50

>2000 mg/kg

DERMAL LD50

>2000 mg/kg

INHALATION LC50 (vapours)

>20 mg/L/4H

Toxicity Data

TOXICITY Data			
Ingredient:	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 mg/L/4H
CAS 1174921-73-3	>5000 - Rat	>5000 - Rabbit	-



Date of issue: 4.02.22 NZ Safety Data Sheet

12. Ecological Information

This product is classified as Ecotoxic according to the criteria of HSNO.

Harmful to aquatic life with long lasting effects.

Ecotoxicity Data - IKO

Product Calculated Aquatic Ecotoxicity – L(E)C50: >10 - ≤100 mg/L:

Ingredients contributing to Aquatic Ecotoxicity:

Ingredient	Classification
CAS 1174921-73-3	Chronic, cat 3

Persistence & Degradability	No data
Mobility	No data
Bioaccumulative Potential	No data
Other	No data

13. Disposal Considerations.

Do not let this product enter the environment. Do not dispose of in waterways or sewers. Dispose of this material and its container as hazardous waste, via a licensed facility. See local council for disposal/recycling information.

14. Transportation Information.

Regulated for transport Keep separated from foodstuffs

UN Number: 1268

Proper Shipping Name: PETROLEUM PRODUCTS, NOS (Aliphatic Hydrocarbons)

Class: 3
Packing Group: III
Hazchem: 3Y
Marine Pollutant: No



15. Regulatory Information.

Group Standard: HSR002662
Surface Coatings & Colorants - Flammable

HSNO CONTROLS

SDS required when any quantity is present in a workplace.

At least 2 x 4.5kg powder fire extinguishers required when 500L is present in a workplace.

Emergency Response Plan and Secondary Containment required when >1000L is present in a workplace

Flammable signage required when >1000L is stored.

Ecotoxic signage required when >1000L is stored.

NURAFLUX PRIMER QD



Date of issue: 4.02.22 NZ Safety Data Sheet

(Flam Liq, Cat 3) Hazardous Substances Location	>500L (closed containers >5L)
Compliance Certificate required for:	>1500L (closed containers up to 5L)
	>250L (open containers)
(Flam Liq, Cat 3) Hazardous Atmosphere Zone	>100L (closed containers)
required for:	>25L (decanting)
	>5L (open occasionally
	>1L (open containers in continuous use)
Certified Handler	Not Required
Tracking	Not Required
	· · · · · · · · · · · · · · · · · · ·

All ingredients are on the New Zealand Inventory of Chemicals (NZIoC), or exempt.

Any existing national regulations on the handling of dangerous substances should be observed. Controls for hazardous substances are based upon current knowledge. Where multiple chemicals are stored, controls will need to take into account aggregate quantities. Contact a WorkSafe approved Compliance Certifier for further information and guidance.

16. Other Information.

HSNO = Hazardous Substances and New Organisms Act.

EPA = Environmental Protection Authority

Date of SDS Preparation: 4 February 2022 Replaces Version Dated: 19 April 2018

The data given here is based on current knowledge and experience. The purpose of this Safety Data Sheet is to describe products in terms of their safety requirements. The above details do not imply any guarantee concerning composition, properties or performance of the product.