

Glue Guru

SAFETY DATA SHEET

Section 1. Identification of the material and the supplier

Product: CANTAC ROOF-TAC (Sprayable Contact Adhesive)
Product Use: Adhesive for industrial use.
Restriction of Use: Refer to Section 15

New Zealand Supplier: **Glue Guru**
Address: 1016E Great South Road
Penrose, Auckland, 1061
Telephone: 09 444 4878
Fax Number: 09 442 5975
NZ Emergency No: **0800 764 766(National Poison Centre)**

Australian Supplier: **Glue Guru International Ltd**
Address: 2/9 Leakes Road
Laverton North
Melbourne, VIC
Australia
Telephone No: 1300 901 687

Australian Emergency No **13 11 26 (National Poison Centre)**

Date of SDS Preparation: 4 August 2022 v2

Section 2. Hazards Identification

Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

New Zealand:

This product is classified as per EPA Hazardous Substances (Classification) Notice 2020.

EPA Approval Code: Surface Coatings and Colourants (Carcinogenic) - HSR002679

Pictograms



Signal Word: **DANGER**

GHS Category	Hazard Code	Hazard Statement
Flammable gas Cat. 1A	H220	Extremely flammable gas.
Liquefied Gas	H280	Contains gas under pressure may explode if heated.
Skin irritation Cat. 2	H315	Causes skin irritation.
Eye irritation Cat. 2	H319	Causes serious eye irritation.
Carcinogenicity Cat. 2	H351	Suspected of causing cancer.

Product Name: CANTAC ROOF-TAC
Date of MSDS: 11 November 2020

Issued by: Glue Guru
Tel: 64 9 444 4878

Specific target organ toxicity – repeated exposure Cat. 2	H373	May cause damage to organs through prolonged or repeated exposure.
Narcotic effects	H336	May cause drowsiness or dizziness.

Prevention Code Prevention Statement

P103	Read label before use.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, sparks, open flames or hot surfaces. No smoking.
P260	Do not breathe fumes, gas, vapours or spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective clothing as detailed in Section 8.
P281	Use personal protective equipment as required.

Response Code Response Statement

P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P362	Take off contaminated clothing and wash before re-use.
P377	Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381	Eliminate all ignition sources if safe to do so.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.

Storage Code Storage Statement

P403	Store in a well-ventilated place.
P405	Store locked up.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P410 + P403	Protect from sunlight. Store in a well-ventilated place.

Disposal Code Disposal Statement

P501	Dispose of according to the local authorities
------	---

Section 3. Composition of hazardous Ingredients

Ingredients	Wt%	CAS NUMBER.
Dichloromethane	<25	75-09-2
Propane/Isobutane Propellant	Proprietary	74-98-6 75-28-5

Section 4. First Aid Measures

Routes of Exposure:

If in Eyes Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If frostbite, call a physician.

If on Skin In case of contact with liquid, thaw frosted parts with water. Do not attempt to remove clothing which has stuck to the skin. Wash affected area with plenty of soap and water. If irritation (redness, rash, blistering) develops, get medical attention. Call a POISON CENTER/doctor.

If Swallowed Do NOT induce vomiting. If vomiting occurs turn patient on side. IF exposed or concerned: Call a POISON CENTER/doctor.

If Inhaled Remove persons affected by vapour to fresh air. Apply artificial respiration if patient is not breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

Most important symptoms and effects, both acute and delayed:

Symptoms:

Ingestion: Not applicable.

Inhalation: May cause drowsiness or dizziness.

Skin: Causes skin irritation. Do not attempt to remove clothing that adheres to the skin due to freezing.

Eye: Causes serious eye irritation.

Chronic: Suspected of causing cancer

May cause damage to organs through prolonged or repeated exposure

Notes to Doctor: Upon exposure to Dichloromethane: Do not administer any preparations of the adrenaline-ephedrine group.

Section 5. Fire Fighting Measures

Hazard Type	Flammable aerosol canister
Hazards from products	In case of fire, stop leak if safe to do so. Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback. May decompose in a fire, giving off toxic and irritant vapours. Hazardous decomposition product(s): Hydrogen chloride, carbon oxides, Phosgene, Chlorine
Suitable Extinguishing media	Water spray, foam, dry powder or CO2 Do not use water jet. Direct water jet may spread the fire.
Precautions for firefighters and special protective clothing	Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. If possible, remove containers before using water. Keep containers cool by spraying with water if exposed to fire.
HAZCHEM CODE	2YE

Section 6. Accidental Release Measures

Avoid all contact. Use personal protective equipment as detailed in Section 8. Avoid breathing gas. Ensure adequate ventilation. Remove all ignition sources. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Remove clothing and wash thoroughly before use. In case of contact with liquid, thaw frosted parts with water, remove clothing carefully and wash with soap & water. Isolate the area and allow vapours to disperse. For large spills evacuate the area and keep personnel upwind.

Do not allow to enter drains, sewers or watercourses. Contain the spillage. Any large spillage into watercourses must be alerted to the regulatory authority responsible for environmental protection or other regulatory body.

Allow small spillages to evaporate provided there is adequate ventilation. Do not pierce or burn container, even after use. Containers of this material may be hazardous when empty since they retain product residue. Dispose as per Section 13.

Section 7. Handling and Storage

Handling:

- Read label before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat, sparks, open flames or hot surfaces. No smoking.
- Do not breathe gas.
- Wash hands thoroughly after handling.
- Use only outdoors or in a well-ventilated area. Ensure operatives are trained to minimise exposures.
- Contaminated clothing should be thoroughly cleaned.
- Do not eat, drink or smoke at the work place.
- Keep from direct sunlight.
- Do not spray on an open flame or other ignition source.
- Ground/bond container and receiving equipment.
- Avoid release to the environment.
- Wear protective clothing as detailed in Section 8 and avoid direct contact.
- Use personal protective equipment as required.

Storage:

- Store locked up.
- Store in a cool place.
- Store in a well-ventilated place. Keep container tightly closed.
- Keep in the original container.
- Containers which are opened must be carefully resealed and kept upright to prevent leakage.
- Store at room temperature.
- Do not store with acids, bases, strong oxidizing agents. Avoid contact with alkali metals.

Section 8 Exposure Controls / Personal Protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance		TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Dichloromethane	[75-09-2]	50	174	-	-
Propane	[74-98-6]	Simple asphyxiant – may present an explosion hazard			

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices APRIL 2022 13TH EDITION.

Engineering Controls

Ensure adequate ventilation. Store in a cool/low-temperature, well-ventilated.

Personal Protection Equipment



Eyes	Eye protection with side protection (EN 166)
Hands	Wear impervious gloves (EN374).
Skin	Wear suitable coveralls to prevent exposure to the skin.
Respiratory	In case of inadequate ventilation wear respiratory protection. A suitable

	mask with filter type AX may be appropriate.
General	Keep good industrial hygiene. Wear appropriate personal protective equipment, avoid direct contact. Avoid breathing gas. IF exposed: Wash immediately with water. Wash contaminated clothing before reuse. Do not eat, drink or smoke at the work place.

Section 9 Physical and Chemical Properties

Appearance	Blue
Odour	Solvent
Odour Threshold	Not applicable
pH	Not applicable
Boiling Point	40°C
Melting Point	-97 °C - lit.
Freezing Point	Not applicable
Flash Point	-90 °C - closed cup
Flammability	Not applicable
Upper and Lower Explosive Limits	12 - 19%
Vapour Pressure	70psig @ 21.1C
Vapour Density	(AIR =1) 2.15
Relative Density	1.3 g/mL at 25 °C
Solubilities	insoluble
Partition Coefficient: n-octanol/water;	log Pow: 1.25
Auto-ignition Temperature	>556.1°C
Decomposition Temperature	Not applicable
Kinematic Viscosity	Not applicable
Particle Characteristics	Not applicable

Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.
Possibility of hazardous reactions	No data available
Conditions to Avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep from direct sunlight. Keep away from: Elevated temperature. Do not spray on an open flame or other ignition source.
Incompatible Materials	Acids, Bases, Strong oxidising agents. Avoid contact with alkali metals.
Hazardous Decomposition Products	May decompose in a fire, giving off toxic and irritant vapours. Hazardous decomposition product(s): Hydrogen chloride, carbon oxides, Phosgene, Chlorine

Section 11 Toxicological Information

Acute Effects:

Oral	Not applicable. LD 50 = 5640mg/kg
Dermal	Not applicable.
Inhalation	Causes dizziness and drowsiness.
Eye	Causes severe irritation to eyes.

Skin	Causes skin irritation.
-------------	-------------------------

Chronic Effects:

Carcinogenicity	Suspected of causing cancer.
Reproductive Toxicity	Not applicable.
Germ Cell Mutagenicity	Not applicable.
Aspiration	Not applicable.
STOT/SE	Not applicable.
STOT/RE	Causes damage to organs through prolonged or repeated exposure.

Individual component information:

Acute Toxicity:

Chemical Name	Oral – LD50	Dermal – LD50	Inhalation – LC50
Dichloromethane (75-09-2)	1410 mg/kg (rat)	>2000mg/kg (Rat)	52 mg/L/4h (Rat)

Section 12. Ecotoxicological Information

Not expected to be a hazard to the aquatic environment.

Persistence and degradability	Biodegradability Result: < 26 % - Not readily biodegradable. (OECD Test Guideline 301C)
Bioaccumulation	The product has no potential for bioaccumulation.
Mobility in Soil	No data available
Other adverse effects	No data available

Toxicity:

Product: Estimated LC50 (96 hour) > 100 mg/l (Fish)
 Dichloromethane: LC50 (Fathead minnow) 193.00 mg/l – 96h

Do not allow to enter waterways.

Section 13. Disposal Considerations

Dispose of this material and its container to hazardous or special waste collection point.
Precautions or conditions to avoid. Do not pierce or burn container, even after use.

Section 14 Transport Information

This product is classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code) (7th edition).

This product is classified as a Dangerous Good for transport in NZ; NZS 5433:2020



Road, Rail, Sea and Air Transport

UN No	3501
Class - Primary	2.1
Packing Group	Not assigned

Proper Shipping Name	CHEMICALS UNDER PRESSURE FLAMMABLE, N.O.S (contains propane and isobutene)
Marine Pollutant	No

Section 15	Regulatory Information
-------------------	-------------------------------

Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

Not classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

New Zealand:

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

EPA Approval Code: Surface Coatings and Colourants (Carcinogenic) - HSR002679

Trigger Quantities for this substance:

Certified Handler	Not required
Location Certificate	100kg
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	250kg
Emergency Response Plan trigger Quantities	300kg
Secondary Containment trigger Quantities	300kg
Restrictions of use	None

Section 16	Other Information
-------------------	--------------------------

Glossary

Cat	Category
EC ₅₀	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC ₅₀	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD ₅₀	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

References:

Australia:

1. Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.
2. Standard for the Uniform Scheduling of Medicines and Poisons.
3. Australian Code for the Transport of Dangerous Goods by Road & Rail.
4. Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.
5. Workplace exposure standards for airborne contaminants, Safe work Australia.
6. American Conference of Industrial Hygienists (ACGIH).

7. Globally Harmonised System of classification and labelling of chemicals.

New Zealand:

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices April 2022 edition.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2020
5. HSW (Hazardous Substances) Regulations 2017

Disclaimer

This document has been issued by the Glue Guru and serves as their Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to the Glue Guru or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While Glue Guru have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, Glue Guru accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the New Zealand distributor, Glue Guru, if further information is required.

Issue Date: 4 August 2022

Review Date: 4 August 2027