

## TECHNICAL DATA SHEET

### PRODUCT DESCRIPTION

Use: To easily form flashings around corners and penetrations. Specifically designed for use in areas that cannot be properly detailed with TPO field membrane.

Material: Flexible, non-reinforced TPO (thermoplastic polyolefin).

Colour: Grey, White

### PHYSICAL PROPERTIES

Tear Resistance (min)	52.5kN/m <sup>2</sup>
Weight per Unit	1.25kg/m <sup>2</sup>

### PACKAGING AND DIMENSIONS

Roll Size	61cm x 1.524m
Nominal Thickness	1.5mm +10%
Coverage per Roll	9.29m <sup>2</sup> (gross)
Weight per Roll	16.3kg

### LIMITATIONS

Do not install Nuraply TPO Detail Membrane in direct contact with asphalt.

Refer to the Nuraply TPO application instructions and detail drawings.

### STORAGE

Store indoors, out of direct sunlight, in a cool, dry location.

### WARRANTY INFORMATION

Approved for use in any Nuraply TPO Membrane Warranty

The information in this product data sheet is based on our experience and testing. It represents the latest information available at the time of printing, but no guarantee of its accuracy is made or implied, nor responsibility taken for use to which this information may be put. We reserve the right to alter or up-date information parameters and formulations at any time without notice.

