
NURAFLUX NO 10 TECHNICAL DATA SHEET

DESCRIPTION

Nuraflux No 10 adhesive is a water based adhesive designed to bond Nuraply bitumen roofing membranes to concrete, plywood and timber. It features good initial grab with excellent exterior weathering resistance.

SPECIFICATION

Type:	Modified synthetic latex / bitumen emulsion.
Colour:	Black.
Viscosity:	Brushable or spreadable.
Solids:	55% approx.
Cleaner:	Water while wet, Bostik Solvent No.2 or 3 when dry
Stability:	Protect from frost. Not freeze-thaw stable.

APPLICATION

All surfaces must be clean and free from grease, oil, release agents or dust etc. It can be applied using brush, roller.

NOTE: Concrete must be cured for a minimum of 27 days and have a moisture content of 18% or less. Plywood and timber must have a moisture content of 18% or less and be of the correct standards.

PACKAGING

15 litres plastic pail

STORAGE

Store in cool, dry conditions out of direct sunlight between 5° C and 25° C. This product MUST be protected from frost.

SHELF LIFE

12 months under normal temperature conditions and in original containers.

The information in this product data sheet is based on our experience and testing. It represents the latest information available at the time of printing, but no guarantee of its accuracy is made or implied, nor responsibility taken for use to which this information may be put. We reserve the right to alter or up-date information parameters and formulations at any time without notice.