

TECHNICAL DATA SHEET

DESCRIPTION

PREPRUFE® Detail Tape is a specially formulated, two-sided, highly aggressive tape. It is a 50 mm wide x15 m long self-adhesive tape with a release liner.

- PREPRUFE® Detail Tape is provided in Low Temperature and Hot Climate Grades as follows:
- PREPRUFE® Detail Tape LT Grade — for temperatures between -4°C and +30°C
- PREPRUFE® Detail Tape HC Grade — for use in Hot Climates (minimum +10°C)

TECHNICAL SPECIFICATIONS

Technical Specifications	Unit of Measurement
ROLL SIZE	50mm x 15.0m

AREA OF USE

PREPRUFE® Detail Tape is ideally suited for the following uses:

- As a detailing accessory to the PREPRUFE® and Systems
- Adhering NURADRAIN drainage sheet and ENERTHERM PIR insulation boards to waterproofing membranes

INSTRUCTIONS FOR USE:

SAFETY, STORAGE AND HANDLING INFORMATION

PREPRUFE® products must be handled properly. Vapours from solvent-based primers and mastic are harmful and flammable. For these products, the best available information on safe handling, storage, personal protection, health, and environmental considerations has been gathered. SDS (Safety Data Sheet) are available [here](#) and users should acquaint themselves with this information. Carefully read detailed precaution statements on product labels and the SDS before use.

PRODUCT APPLICATION

Surface Preparation

All surfaces must be clean, dry, and free from dirt, grease, oil, dust or other contaminants.

PREPRUFE® Systems

PREPRUFE® Detail Tape must be rolled firmly into place prior to removing the release liner. Ensure the release liner is then removed prior to adhering the next piece of membrane to the PREPRUFE® Detail Tape, which then must be rolled into place as well over the PREPRUFE® Detail Tape. Refer to applicable system detail drawings at <https://www.nuralite.co.nz/index>

NURADRAIN drainage sheet

Where NURADRAIN drainage sheet is placed horizontally from rolls onto a wall, a continuous strip of PREPRUFE® Detail Tape near the top and another strip near the bottom is recommended. If the drainage composite is cut and applied vertically in 1.8 to 2.4 m lengths, a strip is recommended near the top, another near the middle and a third near the bottom.

TECHNICAL DATA SHEET

ENERTHERM PIR insulation board

On walls, apply a strip of tape near the top and bottom edge of the board or insulation. If the board is applied vertically in lengths of 2.4m or more, apply a third strip of tape in the middle of the board or insulation. Press panel firmly over the tape to ensure a good bond.

SHELF LIFE

12 months.

TRANSPORT CLASSIFICATION

N/A

The information in this product data sheet is based on our experience and testing. It represents the latest information available at the time of printing, but no guarantee of its accuracy is made or implied, nor responsibility taken for use to which this information may be put. We reserve the right to alter or up-date information parameters and formulations at any time without notice.