

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Use: To strip in metal flanges on Nuraply TPO Membrane systems or as directed by Waterproofing Systems.

Material: 0.76mm thick, non-reinforced TPO (thermoplastic polyolefin) membrane with a 0.76mm thick, factory-applied peel and stick adhesive tape.

Colour: Grey, White

INSTALLATION/APPLICATION

Prime Nuraply TPO membrane with Nuraply TPO Membrane Primer or Nuraply TPO Single Ply Membrane Primer. (Low VOC) before applying Nuraply TPO Cover Tape.

Refer to the Nuraply TPO application instructions and detail drawings.

PACKAGING AND DIMENSIONS

Roll Size 15.24cm x 30.48m
Thickness Membrane 0.76mm, Tape 0.76mm Total = 1.52mm

STORAGE

Shelf Life 18 months from manufacture date
Storage Conditions Store indoors, out of direct sunlight, in original unopened containers.
Temperature Range 16oC - 27oC

WARRANTY INFORMATION

Approved for use in any Nuraply TPO Membrane Warranty.

The information in this product data sheet is based on our experience and testing. It represents the latest information available at the time of printing, but no guarantee of its accuracy is made or implied, nor responsibility taken for use to which this information may be put. We reserve the right to alter or up-date information parameters and formulations at any time without notice.

