# PRODUCT DESCRIPTION

- Use: To remove dirt, asphalt or other contaminants from Nuraply TPO membranes to ensure a good weld or bond.
- Type: One-part solvent, membrane cleaning agent.
- Colour: Clear

# LIMITATIONS

Membranes or flashings that have been exposed to weather or the elements longer than 7 days must be cleaned with Nuraply TPO Membrane Cleaner prior to welding.

Refer to the application instructions for proper utilization of this cleaner.

# PACKAGING AND COVERAGE

Container Size18.93l pail / 3.79lCoverage Rate \* (2-sided)9.82m2/lShipping Weight (approx.)16.33 kg / 3.25kg

Coverage, open and dry time rates can vary dramatically depending on the particular substrate and environmental conditions. Coverage rates stated herein are approximate only.

### PHYSICAL PROPERTIES

Weight per Unit (approx.) 0.84 kg/l Specific Gravity 0.870

# STORAGE

Shelf Life	12 months from manufacture date
Storage Conditions	Clean, dry, indoor environment, out of direct sunlight, in an unopened container
Temperature Range	16OC-27OC - Protect from freezing

### ENERGY AND THE ENVIRONMENT

Maximum VOC <650 g/l (EPA Method 24)

### PRECAUTIONS

This product is a flammable material and should be shipped and stored away from open flames, heat or sources of ignition.

Keep all pails tightly sealed while in storage. It should be used only in well-ventilated areas. It may cause eye, skin and respiratory irritation, and is harmful or fatal if swallowed. Avoid contact with skin. Use impervious clothing and rubber gloves to avoid prolonged or repeated contact with skin. Read the container label and follow all safety instructions.

The information in this product data sheet is based on our experience and testing. It represents the latest information available at the time of printing, but no guarantee of its accuracy is made or implied, nor responsibility taken for use to which this information may be put. We reserve the right to alter or up-date information parameters and formulations at any time without notice.

